

FUME DOESN'T STAND A CHANCE

MOBIFLEX® MOBILE WELDING FUME EXTRACTORS

Mobiflex® 400-MS with
required Extraction Arm

Mobiflex® 200-M with
required Extraction Arm



KEY FEATURES

The Mobiflex® 200-M and 400-MS are low vacuum welding fume extraction and filtration systems. The mobile system is ideal for smaller manufacturing facilities that require light to medium duty welding fume extraction⁽¹⁾ in variable locations.

- » Generous airflow and larger filter capacity requires less change outs
- » Filter status indicator monitors the amount of particulate in the filter cartridge to alert the user for filter maintenance or replacement
- » Choose from a variety of extraction arms or a hose/hood set

⁽¹⁾ Not suitable for use with cutting, oxy-fuel or arc gouging operations.

Processes »

Stick, TIG, MIG, Flux-Cored

Product Number »

Mobiflex 200-M:
K1653-4 (Base Unit, MERV 14 Filter)
K1653-5 (Base Unit, MERV 16 Filter)
K2497-12 (Base Unit Export, MERV 14 Filter)

Mobiflex 400-MS:
K1741-1 (Base Unit, MERV 14 Filter)
K1741-2 (Base Unit, MERV 16 Filter)
K2497-4 (Base Unit Export, MERV 14 Filter)

Input »



Export Models 400-MS Models



KEY FEATURES Continued

- » **Internal spark arrestor** - Functions as a pre-filter for larger sized particulate, prevents sparks from reaching the filter.
- » **Mobiflex 200-M** - Filter status indicator is a color-coded visual guide to show remaining filter life.
- » **Mobiflex 400-MS** - RotaPulse® is an automatic filter cleaning system to extend filter life and reduce maintenance. (Compressed air required)

WHAT'S INCLUDED

Base Units

- » **Filter**
- » **Plastic Housing**
- » **2 ft (0.6 m) Flexible Hose**

RECOMMENDED ACCESSORIES

General



Fume Extraction Arms
These flexible, lightweight extraction arms are rugged, reliable, and dent and scratch resistant. Built with the welder in mind, the arms come equipped with the 360° rotatable hood for optimal positioning.
Order
LFA 3.1 (10 ft) and LFA 4.1 (13 ft) Extraction Arm

K2633-5 LFA 3.1

K2633-6 LFA 3.1 with arc sensor / lamp kit

K2633-7 LFA 4.1

K2633-8 LFA 4.1 with arc sensor / lamp kit



Hose and Hood Set
Length 16.4 ft (5 m)
Diameter 8 in (203 mm)
Order
K1668-3



Mobiflex 200-M Replacement Filters
MERV 14 Filter
Order
KP1673-1



MERV 16 (HE) Filter
Order
KP1673-9



Pre-Filter
Order
KP1673-5



Activated Carbon Filter (optional)
Fits over KP1673-1 and KP1673-3
Order
KP1852-1



Mobiflex 400-MS Replacement Filters
MERV 14 Filter
Order
KP1673-2



MERV 16 (HE) Filter
Order
KP1673-4



Pre-Filter
Order
KP1673-6

PACKAGES – WHAT'S INCLUDED

● Included

Description	Product Number	Mobiflex 200-M Base Unit		Arm Size/Type			
		MERV 14 Filter (K1653-4)	MERV 16 Filter (K1653-5)	LFA 3.1 10 ft (3 m) (K2633-5)	LFA 3.1 10 ft (3 m) with Arc Sensor/ Lamp Kit (K2633-6)	LFA 4.1 13 ft (4 m) (K2633-7)	LFA 4.1 13 ft (4 m) with Arc Sensor/ Lamp Kit (K2633-8)

Mobiflex 200-M with MERV 14 Filter

Mobiflex 200-M with LFA 3.1 10 ft (3 m) Arm One-Pak	K4259-2	●		●			
Mobiflex 200-M with LFA 3.1 10 ft (3 m) Arm and Arc Sensor/Lamp Kit One-Pak	K4259-3	●			●		
Mobiflex 200-M with LFA 4.1 13 ft (4 m) Arm One-Pak	K4259-4	●				●	
Mobiflex 200-M with LFA 4.1 13 ft (4 m) Arm and Arc Sensor/Lamp Kit One-Pak	K4259-5	●					●

Mobiflex 200-M with MERV 16 Filter

Mobiflex 200-M with LFA 3.1 10 ft (3 m) Arm One-Pak	K4259-6		●	●			
Mobiflex 200-M with LFA 3.1 10 ft (3 m) Arm and Arc Sensor/Lamp Kit One-Pak	K4259-7		●		●		
Mobiflex 200-M with LFA 4.1 13 ft (4 m) Arm One-Pak	K4259-8		●			●	
Mobiflex 200-M with LFA 4.1 13 ft (4 m) Arm and Arc Sensor/Lamp Kit One-Pak	K4259-9		●				●

PRODUCT SPECIFICATIONS

Product Name	Product Number	Filter Type	Filter Size ft ² [m ²]	Input Power Voltage/Phase/Hertz	Input Current	Dimensions H x W x D in. (mm)	Weight lbs. (kg)	
Mobiflex 200-M with MERV 14 Filter Base Unit	K1653-4	Cellulose	538 (50)	115/1/50/60	7.2A	36 x 32 x 48 (900 x 810 x 1210)	216 (98)	
Mobiflex 200-M (MERV 14 Filter) LFA 3.1 10 ft. Single Arm One-Pak®	K4259-2						249 (112.9)	
Mobiflex 200-M (MERV 14 Filter) LFA 3.1 10 ft. Arm and Arc Sensor/Lamp Kit One-Pak	K4259-3							
Mobiflex 200-M (MERV 14 Filter) LFA 4.1 13 ft. Arm One-Pak	K4259-4						250 (113.4)	
Mobiflex 200-M (MERV 14 Filter) LFA 4.1 13 ft. Arm and Arc Sensor/Lamp Kit One-Pak	K4259-5						253 (114.6)	
Mobiflex 200-M (MERV 16 Filter) Base Unit	K1653-5						High-Efficiency Cellulose/ Polyester	225 (102.1)
Mobiflex 200-M (MERV 16 Filter) LFA 3.1 10 ft. Arm One-Pak	K4259-6							254 (115.2)
Mobiflex 200-M (MERV 16 Filter) LFA 3.1 10 ft. Arm and Arc Sensor/Lamp Kit One-Pak	K4259-7							258 (117)
Mobiflex 200-M (MERV 16 Filter) LFA 4.1 13 ft. Arm One-Pak	K4259-8							262 (118.8)
Mobiflex 200-M (MERV 16 Filter) LFA 4.1 13 ft. Arm and Arc Sensor/Lamp Kit One-Pak	K4259-9							263 (119.3)
Mobiflex 200-M (MERV 14 Filter) Base Unit Export	K2497-12	Cellulose		230/1/50	3.7A		220 (99.8)	
Mobiflex 400-MS (MERV 14 Filter) Base Unit	K1741-1	Cellulose	325 (30)	115/1/60	12A	40 x 32 x 48 (1020 x 810 x 1210)	255 (115.7)	
Mobiflex 400-MS (MERV 16 Filter) Base Unit	K1741-2						High-Efficiency Cellulose/ Polyester	255 (115.7)
Mobiflex 400-MS (MERV 14 Filter) Base Unit Export	K2497-4	Cellulose		230/1/50	9A		286 (129.7)	

The operation of welding fume control equipment is affected by various factors including proper use and positioning of the equipment, maintenance of the equipment and the specific welding procedure and application involved. Worker exposure level should be checked upon installation and periodically thereafter to be certain it is within applicable OSHA PEL and ACGIH TLV limits.

CUSTOMER ASSISTANCE POLICY

The business of The Lincoln Electric Company® is manufacturing and selling high quality welding equipment, consumables, and cutting equipment. Our challenge is to meet the needs of our customers and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or advice about their use of our products. Our employees respond to inquiries to the best of their ability based on information provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or advice. Moreover, the provision of such information or advice does not create, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information or advice, including any implied warranty of merchantability or any warranty of fitness for any customers' particular purpose is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

Subject to Change – This information is accurate to the best of our knowledge at the time of printing. Please refer to www.lincolnelectric.com for any updated information.

The Lincoln Electric Company
 22801 St. Clair Avenue · Cleveland, OH · 44117-1199 · U.S.A.

www.lincolnelectric.com